

## Floor and wall finishing

### LD 1709 FR

Order no. 256.486



#### The FLEX diamond renovation sander for surfaces

This renovation sander removes layers and concrete slurry coatings really quickly, thanks to the FLEX Thermojet Super diamond grinding pads. It does not rasp or jump, making it ideally suitable for both precision work and large surface removal. The effective turbo vacuum attachment prevents concrete pore clogging. Smearing and sticking is avoided. The surface underground structure is improved during grinding and work accomplished twice as quickly. The innovative dust evacuation guard with a detachable flexible brush ring permits to grind right up to the wall.

Technical attributes	LD 1709 FR
Disc Ø	125 mm
Speed without load	10000 rpm
Power input	1400 Watt
Power output	950 Watt
Tool fixture	M 14
Weight	2,90 kg

Standard equipment	
Thermojet Super 125 Ø	304.727
Clamping nut	100.080
Clamping flange SW 14	191.612
Guard	254.213
Bail handle	236.934
Cable clip	252.188 (3x)
Hose clip	252.050
Vacuum ring	257.246
1 hexagon socket screw key, special tool 4	102.229
Wrench holder	233.943
1 pin wrench	107.492
1 metal carrying case	306.207

#### Advantages at a glance

- FLEX four-fold FR electronic control: with consistent speed control by tachometer generator, soft start, overload protection and temperature monitoring
- Vacuum dust collection: protects against abrasive dust, reduces disc wear, keeps concrete pores for the new coat open
- Flexible rubber vacuum ring: moves smoothly over the surface and protects against dust and stones flying out
- Vacuum attachment: 32 mm exterior Ø
- Spindle lock: for easy disc changes
- Quality shut-off carbon brushes: if the carbon brushes wear down, the motor will be automatically switched off and thus protected from damage

FLEX Elektrowerkzeuge GmbH  
Bahnhofstrasse 15  
D-71711 Steinheim/Murr  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Floor and wall finishing

### LD 3206 C

Order no. 303.798



#### Scouring machine for large areas, 180 mm

- Flexible rubber vacuum ring with low-wear metal ring: moves smoothly over the surface and protects against dust and stones flying out
- Vacuum dust collection: protects against abrasive dust, reduces disc wear, keeps concrete pores for the new coat open
- Vacuum attachment: 32 mm exterior Ø
- Spindle lock
- FLEX Thermojet Super diamond grinding cups rapidly remove all coatings and limewashes
- Ideal for large areas
- Cushioning element between the motor and rear handgrip: significantly reduces vibrations, reducing operator fatigue
- Optimum guidance by rear shaft handle with integrated switch and bail handle
- Suction hose/adapter not included in delivery package

Technical attributes	LD 3206 C
Disc Ø	180 mm
Speed without load	6500 rpm
Power input	2500 watt
Power output	1700 watt
Tool fixture	M 14
Weight	7,60 kg

Standard equipment	
Thermojet Super 180 Ø	303.461
Clamping nut	100.080
Clamping flange SW 17	191.604
Guard	258.625
Bail handle	302.708
Cable clip	302.538 (3x)
Vacuum ring	258.626
1 hexagon socket screw key, special tool 6	256.832
1 pin wrench	100.110
1 pin spanner	258.629
1 plastic carry case	329.908